# SECTION 22 34 38 WATER HEATER, GAS FIRED - ATMOSPHERIC

### PART 1 - GENERAL

- 1.01 RELATED WORK
  - A. Section 22 07 00: Plumbing Insulation
  - B. Section 22 11 16: Domestic Water Piping
  - C. Division 26: Electrical
- 1.02 SUBMITTALS
  - A. Submit product data for review.

### PART 2 - PRODUCTS

- 2.01 ACCEPTABLE MANUFACTURERS
  - A. A.O. Smith
  - B. Lochinvar
  - C. State Industries
  - D. Rheem/Rudd

## 2.02 EQUIPMENT

- A. Carbon steel, glass lined storage tank, ASME Fired Pressure Vessels, code stamped "F" for 150 psi working pressure. Unit shall meet ASHRAE/IES 90.lb-1992 Energy Regulations and Emissions.
- B. Provide the following features:
  - 1. Stainless steel burners and 100% safety shut-off controls
  - 2. ASME temperature and pressure relief valve
  - 3. Fiberglass insulation with steel jacket
  - 4. Operating instructions
  - 5. Parallel arranged heaters supplied with factory manifolds

# PART 3 - EXECUTION

# 3.01 INSTALLATION

- A. Furnish factory or manufacturer's service representative to verify system installation and operation.
- B. Verify location and clearance per local code requirements.
- C. Install in accordance with manufacturer's recommendations and project drawings.
- D. Vent heater to atmosphere in accordance with drawings.
- E. Insulation for water connections in accordance with Section 22 07 00.

Memorial Hermann	Best	<b>Practices</b>
July, 2013		

F. Clean heater and piping.

**END OF SECTION**